

HL1120W Transportable Case for Comms-On-The Pause (COTP) operation

The HL1120W Transportable Case provides rugged, watertight, and dustproof protection for your HL1120W Low Earth Orbit (LEO) equipment during rapid deployment and operation in the field.

Featuring heavy-duty wheels, double throw latches, stainless-steel hardware offering crushproof construction, and ample storage space for IFL cabling, Indoor Unit (IDU) and other auxiliary equipment, it ensures maximum durability and mobility in demanding environments providing safe transport of the HL1120W.

Features

- Case and custom foam padding provide impact protection
- Handles and recessed wheels
- Molded-in, tongue-in-groove gasketed parting lines for splash resistance and tight seals
- Storage for up to 200 feet of IFL or AC power cable
- Airline Transport Rated: ATA Specification 3000 Category 1
- Mildew resistant foam to allow for operation outdoors
- Automatic pressure equalization valve

The standard mounting setup of your HL1120W is still required. Ensure that your fixed or mobile mounts are assembled for quick deployment.

Technical Specifications

Dimensions

Exterior (LxWxD) 37.5 x 27.1 x 14.4 in
(95.3 x 68.9 x 36.5 cm)

Weight

Case (Empty) 41.4 lbs (18.8 kg)
Total Weight (Case + Panel) 94.0 lbs (42.6 kg)
Electronics[†] 58.42 lbs (26.49 kg)

Operating Temperature Range

Minimum Temps -20 °F (-28.9 °C)
Maximum Temps 140 °F (60 °C)

Materials

Body Material Roto-Molded Polypropylene
Handle Heavy Duty Injection Molded Standard

[†]HL1120W Electronics (Outdoor Unit, Indoor Unit, and Power Supply) and cables (IFL or Power) are purchased separately

